

# VS250 SVGA 3LCD Projector

Projectors

Business



## Portable projector with HDMI® for everyday business presentations.

**More accurate, vivid color, even in well-lit rooms** — 3,200 lumens of equal color and white brightness<sup>1</sup>

**SVGA resolution (800 x 600)** — ideal for projecting everyday presentations and graphics

**Fast, easy setup with Epson®** — get up and running in no time with easy image adjustments and convenient control

**Best-in-Class Color Brightness with Epson<sup>2</sup>**

**Works with the latest laptops and media players** — supports HDMI, the standard in connectivity, for digital video and audio in one cable



**Specifications**

**Projection System** 3LCD, 3-chip technology  
**Projection Method** Front/rear/ceiling mount  
**Driving Method** Poly-silicon TFT Active Matrix  
**Pixel Number** 480,000 dots (800 x 600) x 3  
**Color Brightness<sup>1</sup>** Color Light Output: 3,200 lumens  
**White Brightness<sup>1</sup>** White Light Output: 3,200 lumens  
**Aspect Ratio** 4:3  
**Native Resolution** 800 x 600 (SVGA)  
**Resize Support** 1024 x 768 (XGA), 1152 x 864 (SXGA), 1280 x 800 (WXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1440 x 900 (WXGA+), 1400 x 1050 (SXGA+)  
**Lamp Type** 210 W UHE  
**Lamp Life<sup>4</sup>** Up to 6,000 hours (Normal Mode) and up to 10,000 hours (ECO Mode)  
**Throw Ratio Range** 1.45 (Zoom: Wide), 1.96 (Zoom: Tele)  
**Size (Projected Distance)** 30" – 350" (0.88 – 10.44 m)  
**Keystone Correction Auto** Vertical: ± 30 degrees  
**Keystone Correction Manual** Horizontal: ± 30 degrees (Easy-Slide Horizontal Image Correction)  
**USB Plug 'n Play**  
 Projects audio and video, PC and Mac<sup>®</sup> compatible  
**Contrast Ratio** Up to 15,000:1  
**Color Reproduction** Up to 1.07 billion colors

**Projection Lens**

**Type** Digital zoom (Manual)/Focus (Manual)  
**F-number** 1.44  
**Focal Length** 16.7 mm  
**Zoom Ratio** Digital zoom 1.0 – 1.35

**Other**

**Display Performance** NTSC: 480 lines; PAL: 576 lines (Depends on observation of the multi-burst pattern)  
**Input Signal** NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM  
**Speaker** 2 W (mono)  
**Operating Temperature** 41 ° to 95 °F (5 ° to 35 °C)  
**Power Supply Voltage** 100 – 240 V ± 10%, 50/60 Hz  
**Power Consumption**  
 Normal Mode: 296 W  
 ECO Mode: 211 W  
**Fan Noise**  
 Normal Mode: 37 dB  
 ECO Mode: 28 dB  
**Security** Password Protect function

**Dimensions (W x D x H)**

**Including Feet** 11.9" x 9.2" x 3.2"  
**Excluding Feet** 11.9" x 9.2" x 3.0"  
**Weight** 5.3 lb

**Interfaces**

1x HDMI  
 Computer/component video: 1x D-sub 15 pin  
 Composite video: 1x RCA (Yellow)  
 Audio in: 1x RCA (White/Red)  
 1x USB connector Type A: PC-free USB and other  
 1x USB connector Type B: USB Plug 'n Play



**Remote Control**

**Features** Source search selection, power, volume, e-zoom, A/V Mute, freeze, menu, page up and down, help, auto, mouse functions  
**Operating Angle**  
 Right/left: ± 30 degrees  
 Upper/lower: ± 15 degrees  
**Operating Distance** 19.7 ft (6 m)

**Eco Features**

RoHS compliant  
 Recyclable product<sup>5</sup>  
 Epson America, Inc. is a SmartWay<sup>®</sup> Transport Partner<sup>6</sup>

**Support**

**Epson Connection<sup>SM</sup>**  
 Pre-sales support: U.S. and Canada 800-463-7766  
 Internet website: [www.epson.com](http://www.epson.com)  
**Service Programs** 1-year projector limited warranty, Epson Road Service program, PrivateLine<sup>®</sup> dedicated toll-free support and 90-day limited lamp warranty

**What's in the Box**

VS250 projector, power cable, computer cable (VGA), projector remote control, batteries, User Manual CD, Quick Setup Sheet

**Ordering Information**

VS250 Projector	V11H838220
Genuine Epson Lamp (ELPLP96)	V13H010L96
Replacement Air Filter (ELPAF32)	V13H134A32
Soft Carrying Case (ELPKS69)	V12H001K69
Universal Projector Ceiling Mount	ELPMBPJF
Duet <sup>TM</sup> Screen	ELPSC80F
ES3000 Screen (ELPSC26H)	V12H002S3Y
ES1000 Screen	V12H002S4Y

<sup>1</sup> Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | <sup>2</sup> Color Brightness measured per IDMS 15.4. Additional colors and picture modes tested. Top-selling Epson 3LCD projectors vs. comparable top-selling 1-chip DLP projectors based on NPD sales data for May 2017 – April 2018. COLOR BRIGHTNESS WILL VARY BASED ON USAGE CONDITIONS. | <sup>3</sup> Based on TFCinfo: U.S. Projector Brand Customer Perception and Preference Study, Multimedia Projectors 2017. | <sup>4</sup> Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. | <sup>5</sup> For convenient and reasonable recycling options, visit [www.epson.com/recycle](http://www.epson.com/recycle) | <sup>6</sup> SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Better Products for a Better Future<sup>™</sup>  
[eco.epson.com](http://eco.epson.com)



Epson America, Inc.  
 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited  
 185 Renfrew Drive, Markham, Ontario L3R 6G3

[www.epson.com](http://www.epson.com)  
[www.epson.ca](http://www.epson.ca)

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark, Duet is a trademark and Epson Connection is a service mark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2019 Epson America, Inc. Com-SS-Oct-13 CPD-53758R1 3/19

**Contact:**

