3M[™] LED advanced light BR-30



Features:

- 12 watts replaces 75W incandescent lamps
- Dimmable to 5% with most incandescent dimmers
- 50,000-hour life, 5-year warranty
- No UV or IR radiation
- 0.9 power factor
- Voltage: 120 VAC
- Socket Type: medium screw base
- Environment: dry locations
- Length: 5.25 in, 134 mm
- Diameter: 3.75 in, 95 mm
- Weight: 12.5 oz, 354 g

The 3M[™] LED advanced light BR-30 is an energy-efficient downlight designed to last 50,000 hours. These dimmable bulbs require just 12 watts to match the lumens in traditional 75W incandescent bulbs. Their smooth beam patterns and warm, white light are ideal for general illumination in a wide range of residential and hospitality applications.












Catalog #	Lumens	CCT (deg K)	Power (W)	Beam Angle	CRI	
RCBR30B27	810	2700	12	Flood	82	
RCBR30B3	830	3000	12	Flood	82	




$3M^{\scriptscriptstyle\mathsf{TM}}$ LED advanced light BR-30


Candela Distribution



Beam Distribution



0° Aiming Footcandles



Ordering Information

	Catalog #	Description	Stock Number	Billing Unit	Case Qty.	MOQ	Item UPC	Case UPC	Case Dimension (L x W x H)	Case Weight (lbs.)	Case Cube (cu. ft.)
	RCBR30B27	BR-30 2700K, Flood, Dimmable	70-0800- 3007-8	EA	16	1 case	000-51128- 94397-7	500-51128- 94397-2	17.1" x 8.6" x 10.5"	10	0.894
	RCBR30B3	BR-30 3000K, Flood, Dimmable	70-0800- 3008-6	EA	16	1 case	000-51128- 94398-4	500-51128- 94398-9	17.1" x 8.6" x 10.5"	10	0.894

LIMITED REMEDY: Warranted to last 5 years based on 12 hours normal use per day at 120 V. 3M makes no other warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose. At 3M's option, refund or replacement is the sole remedy. This Limited Warranty does not cover accident, neglect, abuse, misue or acts of God. LIABILITY FOR DIRECT, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES IS EXPRESSLY EXCLUDED, except where prohibited by law. For warranty claims and additional details, please visit www.3MLighting.com/LED.