# Xerox<sup>®</sup> WorkCentre<sup>®</sup> 3335/3345 Multifunction Printer







System Specification	WorkCentre 3335	WorkCentre 3345	
<b>One-Sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 35 ppm Up to 33 ppm Up to 28 ppm	Up to 42 ppm Up to 40 ppm Up to 34 ppm	
Two-Sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 17 ppm Up to 16 ppm Up to 14 ppm	Up to 21 ppm Up to 20 ppm Up to 17 ppm	
Monthly Duty Cycle <sup>1</sup>	Up to 50,000 pages / month	Up to 80,000 pages / month	
Recommended Average Monthly Print Volume <sup>2</sup>	1,000 to 2,500 pages	2,000 to 4,500 pages	
Processor	1 GHz		
Memory	1.5 GB	1.5 GB	
Connectivity	USB 2.0 10/100/1000Base-T Ethernet Wi-Fi		
Paper Handling	WorkCentre 3335	WorkCentre 3345	
Document Feeder			
Capacity <sup>3</sup>	Automatic Document Feeder (ADF): 50 sheets	Reversing Automatic Document Feeder (RADF): 50 sheets	
Sizes	Custom Sizes: 5.6 x 5.8 in. to 8.5 x 14 in. / 142 x 148 mm to 216 x 356 mm		
Weights	16 lb. to 28 lb. bond / 60 to 105 gsm	12.5 lb. to 28 lb. bond / 50 to 105 gsm	
Bypass Tray			
Capacity <sup>3</sup>	50 sheets	50 sheets	
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm		
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm		
Media Types	Archive Bond Card Stock Custom Envelopes Heavyweight Labels Lightweight Plain Preprinted Recycled Transparencies		
Tray 1			
Capacity <sup>3</sup>	250 sheets		
Sizes	Custom Sizes 3.9 x 5.8 in. to 8.5 x 14 in. / 99 x 147 mm to 216 x 356 mm		

Tray 1			
Weights	16 lb. bond to 43 lb. bond / 60 to 163 gsm		
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled		
Additional Tray			
Capacity <sup>3</sup>	550 sheets		
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm		
Weights	16 lb. to 43 lb. bond / 60 to 163 gsm		
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled		
Total Capacity			
Device Standard Capacity <sup>3</sup>	300 sheets		
Device Total Capacity <sup>3</sup>	850 sheets		
Paper Output	per Output		
Output Capacity <sup>3</sup>	150 sheets		
Automatic 2-Sided	Standard		
Device Specification	WorkCentre 3335	WorkCentre 3345	
Electrical Requirements			
North America	110-127 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 7A		
Europe	220-240 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 5A		
Power Consumption			
Operation <sup>4</sup>	Maximum 700 watts		
Standby Mode <sup>4</sup>	Maximum 50 watts		
Power Off Mode <sup>4</sup>	Maximum 0.1 watts		
Sleep Mode <sup>4</sup>	Maximum 3.5 watts		
Warm-up (from Sleep Mode)	As fast as 35 seconds		
Operating Environment			
Required Temperature Range Storage Operating	32°F to 104°F / 0°C to 40°C 50°F to 90°F / 10°C to 32°C		
Required Reletive Humidity	20% to 80%		
Sound Power Levels Operating Standby	55 dB(A) or less 26 dB(A) or less	57 dB(A) or less 26 dB(A) or less	
Sound Pressure Levels Operating Standby	55 dB(A) or less 26 dB(A) or less	57 dB(A) or less 26 dB(A) or less	
Dimensions and Weight (unpackage	Dimensions and Weight (unpackaged)		
WorkCentre 3335	Width: 16.3 in. / 414.6 mm Depth: 16.6 in. / 420.6 mm Height: 17.7 in. / 449 mm Weight: 34.19 lb. / 15.51 kg		

Dimensions and Weight (unpackaged)		
WorkCentre 3345	Width: 18.5 in. / 469 mm  Depth: 17.5 in. / 444.3 mm  Height: 19 in. / 482.6 mm	
	Weight: 38.07 lb. / 17.27 kg	
550-sheet Paper Tray	Width: 14.4 in. / 366 mm  Depth: 17.9 in. / 454 mm  Height: 5.7 in. / 146 mm  Weight: 11.82 lb. / 5.36 kg	
Dimensions and Weight (packaged)		
WorkCentre 3335	Width: 21 in. / 533 mm  Depth: 21.6 in. / 549 mm  Height: 23.6 in. / 600 mm  Weight: 46.5 lb. / 19.26 kg	
WorkCentre 3345	Width: 23.1 in. / 588 mm Depth: 21.6 in. / 549 mm Height: 24.6 in. / 626 mm Weight: 47.1 lb. / 21.4 kg	
550-sheet Paper Tray	Width: 22.2 in. / 563 mm Depth: 19.6 in. / 497 mm Height: 11.2 in. / 285 mm Weight: 16.8 lb. / 7.62 kg	
System Certification/Regulatory Co	mpliance	
Certifications	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5 UL 60950-1/CSA 60950-1-07, 2nd Edition Section 508 NOM GS Mark EAC RoHS Directive 2011/65/EU WEEE Directive 2012/19/EU Citrix Certified Cerner (undergoing evaluation) Apple® AirPrint® 1.5 certification Google Cloud Print 2.0 Certification Mopria certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR® ECOLOGO® EPEAT (United States) To view the latest list of certifications, go to www.xerox.com/OfficeCer	tifications.
Сору	WorkCentre 3335	WorkCentre 3345
Document Scanner	Automatic Document Feeder with 50-sheet capacity	Reversing Automatic Document Feeder with 50-sheet capacity
Document Scanner Size	Platen: Up to 8.5 x 11.7 in / A4 ADF: 8.5 x 14 in. / 216 x 356 mm	Platen: Up to 8.5 x 11.7 in / A4 RADF: 8.5 x 14 in. / 216 x 356 mm
Simplex Speed	Up to 30 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	Up to 40 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm
Duplex Speed	Up to 12 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	Up to 8.4 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm
First-Copy-Out Time	As fast as 13 seconds from the Platen	
Sides (input:output)	1:1 and 1:2	1:1, 1:2, 2:2, and 2:1
Quantity	1 to 999	
Resolution	Up to 600 x 600 dpi	
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments	
Concurrency	Concurrent scanning and printing	

Сору	WorkCentre 3335 WorkCentre 3345		
Copy Features	Automatic Background Suppression Darkness Control ID Card Copy Margin Shift N-up Job Build Photo Mode Program Ahead Booklet Creation Book Copying with Center Erase Edge Erase Job Interrupt Poster Copying		
Print	WorkCentre 3345 WorkCentre 3345		
First-Page-Out Time	As fast as 6.5 seconds (printing from USB); As fast as 9.5 seconds from print driver		
Resolution  Page Description Languages	Up to 1200 x 1200 dpi image quality  PostScript 3 compatible PCL® 5e, 6 PDF Direct TIFF JPEG		
Maximum Print Area	4 mm from all edges		
Print Features	Watermarks Collation Automatic Two-sided Printing N-up Poster Booklet Print Custom Page Size Fit to Page Scaling Draft Mode Earth Smart Printing Print from USB Job Scheduling Print from Local Drive Save Save and Print		
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL		
Operating Systems	Microsoft® Windows® Vista and later Mac OS™ 10.8.x and later Various Linux® and Unix distributions		
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD  NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)  AppleTalk®: EtherTalk®  Microsoft Windows Networking over IP  Bonjour® / Airprint®  IPv6  Secure FTP  Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP		
Font Capability	136 PostScript fonts 111 scalable PCL fonts 1 Bitmap PCL font		
Mobile Solutions and Mobile Device	Mobile Solutions and Mobile Device Apps		
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		

Mobile Solutions and Mobile Device	Apps	
Xerox <sup>®</sup> Global Print Driver <sup>®</sup>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print <sup>™</sup>	Google Cloud Print connects print devices to the web, enabling users to print notebook computers and any other web-connected device.	the applications they use every day from smartphones, tablets, Chromebook $^{\!\scriptscriptstyleM}$
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	
Scan	WorkCentre 3335	WorkCentre 3345
Capability	Color and Black-and-white	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is trai	nsferring scan to network or fax jobs
Input Speed - Black and White	Scan up to 20 ipm — 8.5 x 11 in. / A4 / 210 x 297 mm	Scan up to 24 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm
Input Speed - Color	Scan up to 6 ipm — 8.5 x 11 in. / A4 / 210 x 297 mm	Scan up to 8 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm
Resolution	Black and White: Optical – 600 x 600 dpi Enhanced up to 4800 x 4800 dpi	
Bit Depth	8-bit Grayscale	
Maximum Scan Area	Platen: Up to 8.5 x 11 in. / A4 Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm	
Network Filing Protocol	FTP SMB/SMB2 SMTP/POP3	
File Formats	PDF Single-page and Multi-page TIFF JPEG BMP	
Scan Driver Compatibility	WIA TWAIN	
Supported Scan Destinations	Scan to Email (SMTP/POP3) Scan to WSD Scan to Application (TWAIN USB/Network) Scan to WSD (USB/WSD Scan) Scan to Mac 10.9 or later (USB/Network/Mac ICA) Scan to USB Scan to Local PC Scan to Network Computer (SMB/FTP) Scan to Folder	
Security	WorkCentre 3335	WorkCentre 3345
Security Features	Secure HTTPS (SSL/TLS) Secure IPP SSL IP Filtering IPv6 SNMP v3 WEP (64-/128-bit) WPA2-PSK (AES) WPA / WPA2-Personal WPA / WPA2-Enterprise Network Address Book Authentication (LDAP, Windows Kerberos)	
WiFi Security		
	Authentication Method  Open WPA PSK WPA PSK / WPA2 PSK WPA Enterprise WPA Enterprise / WPA2™ Enterprise	Encryption  WEP 64 / 128-bit ASCII / HEX  TKIP  AES  TKIP  AES

WiFi Security		
-	WPA Enterprise Authentication Method options:  • PEAPVO MS-CHAPV2  • EAP-TLS  • EAP-TTLS PAP  • EAP-TTLS CHAP	
Fax <sup>5</sup>	WorkCentre 3335	WorkCentre 3345
Fax Speed	33 Kbps	
Memory	5 MB	50 MB
Resolution	Up to 300 x 300 dpi (Super-Fine/Photo) resolution Up to 203 x 196 dpi (Fine) resolution Up to 203 x 98 dpi (Standard) resolution	
Compression	MH/MR/MMR/JBIG/JPEG	
Fax Features	Address Book (Up to 200 speed dials, 209 group dials) Auto Redial Auto Reduction Color Fax Send Delayed Send Fax Forward to Email/Fax Junk fax Protection Memory Receive PC Fax (Windows only) Secure Fax	
Device Management		
Xerox® CentreWare® Web		
Device Status	Web server embedded  Tray status/contents Consumables status	
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete	
Job Submission	Print-ready files (PS, PCL®5c/6, PDF, TIFF Output feature selection	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.	
Browsers	Microsoft® Internet Explorer 6, 7 Firefox® 2., 3 Safari® 3.0	
Xerox® CentreWare® Internet Service	s – Integrated Device Web Page	
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> </ul>	
Remote Print Services		
Xerox® MeterAssistant® ServiceAuto- mated Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consumingend-user involvement and ensures that meter reads are submitted to Xerox on time.	
Xerox® SuppliesAssistant® Ser- viceAutomated Supplies Replenish- ment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster with increased uptime.	
What's In The Box		
	<ul> <li>WorkCentre 3335 Multifunction Printer or WorkCentre 3345 Multifunction Printer</li> <li>Standard Capacity Print cartridge: 2,600 pages<sup>6</sup></li> <li>Software and Documentation CD (with Safety, Regulatory, Recycling and Disposal Guides), Print Drivers and Warranty Statement</li> <li>Installation Guide</li> <li>Quick Use Guides</li> <li>Power cord</li> <li>Fax cord</li> </ul>	

Supplies and Accessories	Quantity	Part Number
Supplies		
Extra-High Capacity Print Cartridges	15,000 standard pages <sup>6</sup>	106R03624
High Capacity Print Cartridges	8,500 standard pages <sup>6</sup>	106R03622
Standard Capacity Print Cartridges	2,600 standard pages <sup>6</sup>	106R03620
Drum Cartridge	30,000 standard pages <sup>7</sup>	101R00555
Accessories		
550-sheet Paper Tray		097N02254
Near Field Communication (NFC) Enablement Kit		097N02255
Card Reader Enablement Kit (with Card Reader)		497K17980
Card Reader Enablement Kit (without Card Reader)		497K17990

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
<sup>2</sup> Expected regular monthly throughput.
<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
<sup>6</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.
<sup>5</sup> Requires analog phone line.

Requires unlaugh priorie line.

Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.





